

CyberPower BP36V60ART2U uninterruptible power supply (UPS)
10 AC outlet(s)

Brand : CyberPower

Product code: BP36V60ART2U

Product name : BP36V60ART2U



Extended Battery Module - 36V / 60A, 6x12V/9AH Sealed lead-acid, 5h, 2U, 22.9kg, Black

CyberPower BP36V60ART2U uninterruptible power supply (UPS) 10 AC outlet(s):

The CyberPower BP36V60ART2U (36V) Extended Battery Module (EBM) with DC plug-n-play connections and Fast Charge Technology provide extended battery run-time during power outages for select Smart App Online UPS models. Up to 10 EBM's can be added and fast charging times are maintained thanks to each EBM having a built in battery charger. The typical charging times of 5 hours for the OL1000RTXL2U and OL1500RTXL2U are maintained whether there are 1 or 10 EBM's installed.

Each EBM takes up 2U of rack space and can also be installed in a tower form factor to match the UPS. A DC plug-n-play power connector makes it easy to daisy-chain additional EBM's to a UPS system.

A Three-Year Warranty ensures that this extended battery module has passed our highest quality standards in design, assembly, material or workmanship.

Features		Operational conditions	
Output operation voltage (min)	36 V	Operating relative humidity (H-H)	0 - 90%
Maximum current	60 A	Storage relative humidity (H-H)	0 - 95%
Ports & interfaces		Operating altitude	0 - 3000 m
AC outlets quantity	10 AC outlet(s)	Non-operating altitude	0 - 15000 m
Battery		Certificates	
Battery technology	Sealed Lead Acid (VRLA)	Compliance certificates	RoHS
Number of battery cells	6	Certification	UL1778, CSA C22.2 NO.107.3-05, FCC DOC A
Battery recharge time	5 h	Weight & dimensions	
Hot-swap battery	✓	Width	433 mm
Design		Depth	430 mm
Form factor *	Rackmount	Height	88 mm
Housing material	Steel	Weight	22.9 kg
Rack capacity	2U	Packaging data	
Product colour *	Black	Package weight	29.6 kg
Operational conditions		Other features	
Operating temperature (T-T)	0 - 40 °C	Battery type	12V/9AH
Storage temperature (T-T)	-15 - 45 °C	Package dimensions (WxDxH)	550 x 590 x 240 mm



0649532604951



649532604951

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.