


Viewsonic 43" 4K Professional Commercial Display with ProAV Integration



Brand : Viewsonic

Product code: CDE4331-1C

Product name : 43" 4K Professional Commercial Display with ProAV Integration

- Fast Warm Boot eliminates long startup delays, launching signage and content in under 7 seconds.
 - Native 4K UHD in Any Orientation delivers sharp, high-resolution visuals in landscape or portrait.
 - USB media playback & scheduling with automatic failover ensures uninterrupted signage
 - Commercial-Grade Brightness & 24/7 Reliability keep content clear and visible around the clock.
 - Centralized control with Pro-AV integration and remote management via Web UI and ViewSonic Manager.
 - Secure, Future-Ready Platform with Android 14, upgradeable OS, Quad-Core SoC, and 8 GB RAM.
- 43", 4K UHD (3840 x 2160), TFT LCD, DLED, 500 nits, 2000:1, 6.5 ms, Quad-core ARM Cortex-A73, 8GB, 32GB, 2x 16 W, HDMI 2.0/2.1, RS-232, WIFI slot, SPDIF, RJ45, USB-A, USB-C, 3.5 mm, Android 14 AOSP

Display		Design	
Panel type	TFT	Bezel width (side)	9.9 mm
LED backlight	✓	Bezel width (top)	9.9 mm
LED backlighting type	Direct-LED	Anti-glare screen	✓
Display diagonal *	109.2 cm (43")	Performance	
Display technology *	LCD	Purpose *	Commercial
Display resolution *	3840 x 2160 pixels	Operating hours (hours/days)	24/7
Display brightness *	500 cd/m²	Power	
HD type *	4K Ultra HD	Power consumption (typical) *	44.58 W
Touchscreen *	✗	Energy efficiency class (SDR)	F
Native aspect ratio	16:9	AC input voltage	100 - 240 V
Response time	6.5 ms	Computer system	
Contrast ratio (typical)	1200:1	Built-in processor *	✓
Contrast ratio (dynamic)	2000:1	Processor manufacturer	ARM
Viewing angle, horizontal	178°	Processor architecture	ARM Cortex-A73
Viewing angle, vertical	178°	Processor cores	4
Active display area (W x H)	941.184 x 529.416 mm	Internal memory	8 GB
Panel life	50000 h	Internal storage capacity	32 GB
Native refresh rate	60 Hz	Operating system installed	Android 14
Haze rate	25%	Weight & dimensions	
Surface hardness	3H	Display width	964.6 mm
Ports & interfaces		Display depth	62 mm
HDMI ports quantity *	4	Display height	552.5 mm
HDMI version	2.0/2.1	Display weight	9.1 kg
HDMI input ports quantity	3	Weight	9.1 kg
HDMI output ports quantity	1	Packaging data	
DVI port *	✗	Package width	1056 mm
DisplayPort version	1.2	Package depth	156 mm
USB port *	✓	Package height	647 mm
USB ports quantity	3	Package weight	13 kg
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Packaging content	
USB connector type	USB Type-A, USB Type-C	Remote control included	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Batteries included	✓
USB Power Delivery (USB PD)	✓	Cables included	AC, HDMI, RS-232
USB Power Delivery up to	65 W	Mounting kit	✓
USB Type-C DisplayPort Alternate Mode	✓	Operational conditions	
Ethernet LAN (RJ-45) ports	2	Operating temperature (T-T)	0 - 40 °C
PC Audio in	✓		

Ports & interfaces		Operational conditions	
RS-232 interface	✓	Operating relative humidity (H-H)	20 - 80%
Digital audio optical out	1	Logistics data	
PC Audio out	✓	Products per master (outer) case	1 pc(s)
Audio		Pallet gross length	114 cm
Built-in speaker(s) *	✓	Pallet gross width	108 cm
Number of built-in speakers	2	Pallet gross height	77.5 cm
RMS rated power	32 W	Harmonized System (HS) code	8528521000
Design		Network	
Product design *	Digital signage flat panel	Ethernet LAN *	✓
Placement supported *	Indoor	Ethernet LAN data rates	10,100,1000 Mbit/s
Orientation	Horizontal/Vertical	Wi-Fi *	✓
Product colour *	Black	Technical details	
Screen shape	Flat	OPS slot	1
VESA mounting *	✓	Sustainability certificates	ENERGY STAR, EPEAT Gold, ErP
Panel mounting interface	200 x 200 mm	Compliance certificates	CB, CE, EAC, Federal
Bezel width (bottom)	9.9 mm		Communications Commission (FCC), RCM, REACH, RoHS, WEEE, cTUVus
Other features			
		Bundled software	AirSync, Manager



766907034691

Catalog Object Cloud