

Allied Telesis GS980M Managed L3 Gigabit Ethernet (10/100/1000) 1U Grey



Brand : Allied Telesis

Product code: AT-GS980M/52-10

Product name : GS980M

48 10/100/1000T switch with 4 SFP slots

Allied Telesis GS980M Managed L3 Gigabit Ethernet (10/100/1000) 1U Grey:

Gigabit Layer 3 Lite Managed Switches

The Allied Telesis CentreCOM GS980M Series of Layer 3 Gigabit switches enable a cost-effective and fully managed network. A high-density, space saving solution, with Power over Ethernet (PoE+) to connect and power devices such as video surveillance cameras and IP phones, makes the GS980M Series ideal for applications at the network edge.

Allied Telesis GS980M. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 48. Full duplex. MAC address table: 16000 entries, Switching capacity: 104 Gbit/s. Networking standards: IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE.... Rack mounting, Form factor: 1U

Management features		Security	
Switch type *	Managed	IGMP snooping	✓
Switch layer	L3	Security algorithms	3DES, AES, MD5, PEAP, RSA, SHA-1, SHA-2, SNMP, SNMPv2, SNMPv3, SSH, SSL/TLS, TTLS
Quality of Service (QoS) support	✓	MAC address filtering	✓
Web-based management	✓	SSH/SSL support	✓
Configuring Location Settings (CLI)	✓	Loop protection	✓
System event log	✓	BPDU filtering/protection	✓
MIB support	SNMP MIB	Authentication	MAC-based authentication, Port-based authentication
Ports & interfaces		Password protection	✓
Basic switching RJ-45 Ethernet ports quantity *	48	Authentication type	AAA, IEEE 802.1x, Network Access Control (NAC), RADIUS
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Multicast features	
SFP module slots quantity	4	Multicast support	✓
Network		Protocols	
Networking standards *	IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Routing protocols	RIP, RIP-2
10G support *	✗	Design	
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T	Rack mounting *	✓
Port mirroring	✓	Form factor	1U
Full duplex	✓	Product colour	Grey
IP routing	✓	Performance	
Flow control support	✓	Memory type	DDR-SDRAM
Link aggregation	✓	Internal memory	512 MB
Broadcast storm control	✓	Flash memory	128 MB
Spanning tree protocol	✓	Noise level	39 dB
IPv4 routes	16	Power	
IPv6 routes	16	Power source *	AC
VLAN support	✓	Power supply included *	✓
Virtual LAN features	Port-based VLAN, Private VLAN, Protocol-based VLAN, Tagged VLAN	Power consumption (max)	47 W
Number of VLANs	4094	Power over Ethernet (PoE)	
Optical fiber		Power over Ethernet (PoE) *	✗
Fiber ethernet cabling technology	100BASE-X, 1000BASE-X		

Data transmission		Operational conditions	
Switching capacity *	104 Gbit/s	Operating temperature (T-T)	0 - 50 °C
Forwarding rate	77.4 Mpps	Storage temperature (T-T)	-25 - 70 °C
MAC address table *	16000 entries	Operating relative humidity (H-H)	5 - 90%
Latency (10-100 Mbps)	5.5 µs	Storage relative humidity (H-H)	5 - 95%
Latency (1 Gbps)	2.6 µs	Operating altitude	0 - 3048 m
Static route	✓	Heat dissipation	160 BTU/h
Jumbo frames support	✓	Weight & dimensions	
Packet buffer memory	3 MB	Width	441 mm
Security		Depth	323 mm
DHCP features	DHCP client, DHCP snooping	Height	44 mm
Access Control List (ACL)	✓	Weight	4.5 kg
		Packaging data	
		Package width	575 mm
		Package depth	445 mm
		Package height	150 mm
		Package weight	6.4 kg



0767035212357



767035212357

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.