



DELL Pro E2026H computer monitor 49.5 cm (19.5") 1600 x 900 pixels HD+ LCD Black

Brand : DELL

Product family: Pro

Product code: DELL-E2026H

Product name : E2026H

- 19.5" LCD TN
- HD+, 16:9, 1600 x 900
- 100Hz, 5ms, 250cd/m²
19.5", 1600 x 900 Edge LED TN, 100Hz, 16:9, 250cd/m², 5ms, 170°/160°

DELL Pro E2026H computer monitor 49.5 cm (19.5") 1600 x 900 pixels HD+ LCD Black:

Designed for everyday productivity, this 19.5-inch monitor features up to 100Hz refresh rate and eye comfort solutions that reduce blue light emissions.

DELL Pro E2026H. Display diagonal: 49.5 cm (19.5"), Display resolution: 1600 x 900 pixels, HD type: HD+, Display technology: LCD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 170°, Viewing angle, vertical: 160°. VESA mounting. Product colour: Black



Display		Power	
Display diagonal *	49.5 cm (19.5")	Energy efficiency class (SDR) *	C
Display resolution *	1600 x 900 pixels	Energy efficiency class (HDR) *	Not available
HD type *	HD+	Energy consumption (SDR) per 1000 hours *	9 kWh
Native aspect ratio *	16:9	Power consumption (typical) *	9.2 W
Display technology *	LCD	Power consumption (standby) *	0.3 W
Panel type *	TN	Power consumption (max)	18 W
LED backlight	✓	Power consumption (off)	0.3 W
Backlight type	Edge LED	AC input voltage	100 - 240 V
Touchscreen *	✗	AC input frequency	50/60 Hz
Display brightness (typical)	250 cd/m ²	Input current	0.7 A
Response time *	5 ms	Power supply type	Internal
Response time measurement type	GTG (Gray to Gray)	Energy efficiency scale	A to G
Anti-glare screen	✓	Operational conditions	
Screen shape *	Flat	Operating temperature (T-T)	0 - 40 °C
Supported graphics resolutions	720 x 480, 640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA),	Storage temperature (T-T)	-20 - 60 °C
	1152 x 864 (XGA+), 1280 x 720 (HD 720), 1280 x 1024 (SXGA), 1600 x 900	Operating relative humidity (H-H)	10 - 80%
Supported video modes	480p, 576p, 720p	Storage relative humidity (H-H)	5 - 90%
	1000:1	Operating altitude	0 - 5000 m
Contrast ratio (typical) *	1000:1	Non-operating altitude	5000 - 12192 m
Maximum refresh rate *	100 Hz	Weight & dimensions	
Viewing angle, horizontal	170°	Width (with stand)	464 mm
Viewing angle, vertical	160°	Depth (with stand)	171 mm
Display number of colours *	16.7 million colours	Height (with stand)	366.5 mm
Pixel pitch	0.2706 x 0.2645 mm	Weight (with stand)	2.51 kg
Pixel density	94 ppi	Width (without stand)	464 mm
Horizontal scan range	30 - 82 kHz	Depth (without stand)	47.1 mm
Vertical scan range	50 - 76 Hz	Height (without stand)	277.1 mm
Viewable size, horizontal	43.3 cm	Weight (without stand)	2.2 kg
Viewable size, vertical	23.8 cm	Bezel width (side)	1.55 cm
Viewable size diagonal	49.5 cm	Bezel width (top)	1.69 cm

Display		Weight & dimensions	
Digital horizontal frequency	30 - 95 kHz	Bezel width (bottom)	1.71 cm
Digital vertical frequency	50 - 100 Hz	Packaging data	
Surface hardness	3H	Package weight	4.09 kg
NTSC coverage (typical)	72%	Packaging content	
Performance		Stand included	✓
Flicker-free technology	✓	Cables included	DisplayPort, Power
Multimedia		DisplayPort cable length	1.8 m
Built-in speaker(s) *	✗	Sustainability	
Built-in camera *	✗	Sustainability certificates	TCO, ENERGY STAR
Design		Doesn't contain	Arsenic, Mercury, PVC/BFR
Product colour *	Black	Carbon footprint	
Ports & interfaces		Total carbon footprint (kg of CO2e)	107
Built-in USB hub *	✗	Carbon emissions, manufacturing (kg of CO2e)	51.15
VGA (D-Sub) ports quantity	1	Carbon emissions, logistics (kg of CO2e)	7.7
HDMI *	✓	Carbon emissions, energy usage (kg of CO2e)	46.01
HDMI ports quantity	1	Carbon emissions, end-of-life (kg of CO2e)	2.14
DisplayPorts quantity	1	PAIA version	GaBi version 1, 2025
DisplayPort out version	1.2	Other features	
Headphone out *	✗	Compliance certificates	RoHS
HDCP	✓		
HDCP version	1.4		
Ergonomics			
VESA mounting *	✓		
Panel mounting interface	100 x 100 mm		
Cable lock slot *	✓		
Cable lock slot type	Kensington		
Height adjustment *	✗		
Tilt adjustment	✓		
Tilt angle range	-5 - 21°		
On Screen Display (OSD)	✓		



0884116691914



884116691914

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.