



TP-Link Omada MC110CS network media converter 100 Mbit/s 1310 nm Single-mode Black



Brand : TP-Link

Product family: Omada

Product code: MC110CS

Product name : MC110CS

- Complies with 802.3u 10/100Base-TX, 100Base-FX standards
 - Auto-negotiation of Half-Duplex / Full-Duplex transfer mode
 - Extends fiber distance up to 12.5 miles (20km)
- 10/100Mbps, Single-Mode, 1310 nm, 12500 m

TP-Link Omada MC110CS network media converter 100 Mbit/s 1310 nm Single-mode Black:

The MC110CS is a media converter designed to convert 100BASE-FX fiber to 100Base-TX copper media and vice versa. Designed under IEEE 802.3u 10/100Base-TX and 100Base-FX standards, the MC110CS is designed for use with single-mode fiber cable utilizing the SC-Type connector. The MC110CS supports longwave (LX) laser specification at a full wire speed forwarding rate. It works at 1310nm on both transmitting and receiving data. Auto MDI/MDI-X for TX port, Auto negotiation of duplex mode. The MC110CS will transmit at extended fiber optic distances utilizing single-mode fiber up to 12.5 miles (20km).

Network		Ports & interfaces	
Maximum data transfer rate *	100 Mbit/s	Fiber ports quantity	1
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	Fiber optic connector *	SC
Ethernet LAN data rates	10,100 Mbit/s	Power	
Copper ethernet cabling technology	10BASE-T, 100BASE-FX, 100BASE-T	Power consumption (max)	2.4 W
Auto MDI/MDI-X	✓	Weight & dimensions	
Duplex system	Full, Half	Width	95 mm
Cable types supported	Cat3, Cat4, Cat5	Depth	73 mm
		Height	27 mm
Performance		Operational conditions	
Maximum transfer distance *	12500 m	Operating temperature (T-T)	0 - 40 °C
Wavelength *	1310 nm	Storage temperature (T-T)	-40 - 70 °C
Fiber mode structure	Single-mode	Operating relative humidity (H-H)	10 - 90%
Features		Storage relative humidity (H-H)	5 - 90%
Internal *	✗	Certificates	
LED indicators	✓	Compliance certificates	RoHS
Product colour	Black	Logistics data	
Ports & interfaces		Harmonized System (HS) code	85176990
Connectivity technology	Wired		
Ethernet LAN (RJ-45) ports	1		



0840460604536



840460604536



1210002611022

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.