

CyberPower PR1000LCD uninterruptible power supply (UPS) 1 kVA 700 W 8 AC outlet(s)

Brand : CyberPower

Product code: PR1000LCD

Product name : PR1000LCD

1000VA, 700W, 6 x NEMA 5-15R Out, 1 x USB, 1 x DB-9, 1 x EPO, EMI/RFI Filters, Mini-Tower
CyberPower PR1000LCD. Output power capacity: 1 kVA, Output power: 700 W, Input operation voltage (min): 75 V. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 7 min, Typical backup time at half load: 24.5 min. Form factor: Mini Tower, Product colour: Black, Cable length: 1.8 m. Compliance certificates: RoHS, Certification: UL1778, cUL 107.3, FCC DOC Class A



Features		Design	
Output power capacity *	1 kVA	Form factor *	Mini Tower
Output power *	700 W	Cable length	1.8 m
Input operation voltage (min) *	75 V	Product colour *	Black
Input operation voltage (max) *	154 V	Display type	LCD
Input frequency *	47/63 Hz	LED indicators	Battery replacement
Surge energy rating	1030 J	Operational conditions	
Emergency Power Off (EPO)	✓	Operating temperature (T-T)	0 - 40 °C
EMI/RFI noise filtering	✓	Operating relative humidity (H-H)	0 - 90%
Power protection features	Overload	Certificates	
Audible alarm(s)	✓	Compliance certificates	RoHS
Ports & interfaces		Certification	UL1778, cUL 107.3, FCC DOC Class A
AC outlet types	NEMA 5-15R	Weight & dimensions	
Power plug	NEMA 5-15P	Width	170.2 mm
AC outlets quantity	8 AC outlet(s)	Depth	431.8 mm
USB 2.0 ports quantity	1	Height	221 mm
Serial ports quantity	1	Weight	20 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Bundled software	PowerPanel
Number of battery cells	2	Other features	
Typical backup time at full load	7 min	Battery type	12V/12AH
Typical backup time at half load	24.5 min	Nominal output voltage	120 V
Battery recharge time	8 h	Compatible operating systems	Windows 2000, 2003, XP 32/64, Vista 32/64, 7, Server 2008.
Hot-swap battery	✓		

Other features

Management platform	SNMP/HTTP
Overload protection	✓



0649532602506



649532602506

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.