

CyberPower PR2200LCDSL uninterruptible power supply (UPS) Line-Interactive 2.07 kVA 1980 W 7 AC outlet(s)

Brand : CyberPower

Product code: PR2200LCDSL

Product name : PR2200LCDSL

2070VA, 1980W, Line Interactive, NEMA 5-20P, NEMA L5-20R, NEMA 5-20R x 6, Mini-Tower
CyberPower PR2200LCDSL. UPS topology: Line-Interactive, Output power capacity: 2.07 kVA, Output power: 1980 W. AC outlet types: NEMA 5-20R, NEMA L5-20R, Power plug: NEMA 5-20P, AC outlets quantity: 7 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 3 min, Typical backup time at half load: 10 min. Form factor: Mini Tower, Product colour: Black, Cable length: 3 m. Compliance certificates: RoHS



Features		Battery	
UPS topology *	Line-Interactive	Typical backup time at full load	3 min
Output power capacity *	2.07 kVA	Typical backup time at half load	10 min
Output power *	1980 W	Battery recharge time	8 h
Waveform *	Sine	Hot-swap battery	✓
Input operation voltage (min) *	75 V	Design	
Input operation voltage (max) *	154 V	Form factor *	Mini Tower
Input frequency *	57/63 Hz	Cable length	3 m
Output operation voltage (max)	120 V	Product colour *	Black
Output frequency	60 Hz	Display type	LCD
Automatic Voltage Regulation (AVR)	✓	LED indicators	✓
Surge energy rating	1030 J	Operational conditions	
Power factor	0.95	Operating temperature (T-T)	0 - 40 °C
Emergency Power Off (EPO)	✓	Storage relative humidity (H-H)	0 - 90%
Power protection features	Overload	Certificates	
Audible alarm(s)	✓	Compliance certificates	RoHS
Ports & interfaces		Safety regulation & standards	
AC outlet types	NEMA 5-20R, NEMA L5-20R	Safety	UL1778 4th, cUL CSA C22.2 No 107.3-05, FCC/DOC Class A
Power plug	NEMA 5-20P	Sustainability	
AC outlets quantity	7 AC outlet(s)	Sustainability certificates	ENERGY STAR
USB 2.0 ports quantity	1	Weight & dimensions	
Serial ports quantity	1	Width	170.2 mm
Battery		Depth	431.8 mm
Battery technology	Sealed Lead Acid (VRLA)	Height	221 mm
Number of batteries supported	4		

Weight & dimensions	
Weight	23.5 kg
Other features	
Output voltage	120 V



0649532610259



649532610259

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.