



TP-Link Omada SM5110LSB-10 network transceiver module Fiber optic 10312 Mbit/s SFP+



Brand : TP-Link

Product family: Omada

Product code: SM5110LSB-10

Product name : SM5110LSB-10

- Supports WDM Bi-Directional technology, using a single strand of fiber, cost saving
 - Single mode SFP+ LC Transceiver
 - Hot-Pluggable with maximum flexibility
 - Supports Digital Diagnostic Monitoring (DDM)
 - Compatible with 10G Small Form Pluggable Multi-Source Agreement (SFP+)
 - Compatible with switches with 10G ports like SG3428X and SG3452X
- 10GBase-BX, WDM Bi-Directional, SFP+, LC, TX: 1270 nm, RX: 1330 nm, 57 x 14 x 12 mm

TP-Link Omada SM5110LSB-10 network transceiver module Fiber optic 10312 Mbit/s SFP+:

The SM5110LSB-10 is designed to extend transmission distance up to 10km with a maximum rate of 10Gbps. It is a single-mode SFP+ transceiver that supports bi-directional data transmission, which is cost-saving.

TP-Link Omada SM5110LSB-10. SFP transceiver type: Fiber optic, Maximum data transfer rate: 10312 Mbit/s, Interface type: SFP+. Product colour: Silver. Input voltage: 3.3 V. Compliance certificates: CE, Federal Communications Commission (FCC), RoHS. Width: 57 mm, Depth: 14 mm, Height: 12 mm

Performance		Certificates	
SFP transceiver type *	Fiber optic	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Maximum data transfer rate *	10312 Mbit/s		
Interface type *	SFP+		
Single-mode fiber (SMF) supported	✓	Operational conditions	
Fiber optic connector	LC (UPC)	Minimum operating temperature	0 °C
Fiber cable diameters supported (core/cladding)	9/125 µm	Maximum operating temperature	70 °C
Maximum transfer distance	10000 m	Operating temperature (T-T)	0 - 70 °C
Tx wavelength (max)	1270 nm	Storage temperature (T-T)	-40 - 85 °C
Rx wavelength (max)	1330 nm	Operating relative humidity (H-H)	10 - 90%
Networking standards	IEEE 802.3ae	Storage relative humidity (H-H)	5 - 90%
Digital Diagnostics Monitoring (DDM)	✓	Weight & dimensions	
Features		Width	57 mm
Product colour	Silver	Depth	14 mm
Hot-swap	✓	Height	12 mm
Power		Packaging content	
Input voltage	3.3 V	Quantity per pack	1 pc(s)
		Manual	✓



8885020622942



0810142821674



810142821674

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.