APC SMC1500C uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 900 W 8 AC outlet(s)





Brand : APC

Product code: SMC1500C

Product name : SMC1500C

- Cold-start capable
- Green mode
- High online efficiency
- LCD Status Display
- Pure sine wave output on battery
- Temperature-compensated battery charging

900 W, 120V, 50/60Hz, 8x NEMA 5-15R, USB, LCD, 219x171x439 mm

APC SMC1500C uninterruptible power supply (UPS) Line-Interactive 1.44 kVA 900 W 8 AC outlet(s):

Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
APC SMC1500C. UPS topology: Line-Interactive, Output power capacity: 1.44 kVA, Output power: 900 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: CSA, CSA C22.2 No. 107.1, ENERGY STAR V1.0 (USA), FCC 15 B, ICES-003, UL 1778

Features	
UPS topology *	Line-Interactive
Output power capacity *	1.44 kVA
Output power *	900 W
Waveform *	Sine
Input operation voltage (min) *	85 V
Input operation voltage (max) *	136 V
Input frequency *	50/60 Hz
Output operation voltage (min)	110 V
Output operation voltage (max)	127 V
Output frequency	50/60 Hz
Surge energy rating	680 J
Hold time (min)	6 ms
Hold time (max)	10 ms
Output voltage Total Harmonic Distortion (THD)	5%
EMI/RFI noise filtering	✔
Noise level	45 dB
Surge protection	✔
Audible alarm(s)	✔
Audible alarm modes	Low battery alarm
Auto-restart	✔

Ports & interfaces	
AC outlet types	NEMA 5-15R
Power plug	NEMA 5-15P
AC outlets quantity	8 AC outlet(s)
USB port	✔

Battery	
Replacement battery cartridge	RBC6

Design	
Form factor *	Tower
Cable length	1.83 m
Product colour *	Black
Display type	LCD

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates	
Compliance certificates	RoHS
Certification	CSA, CSA C22.2 No. 107.1, ENERGY STAR V1.0 (USA), FCC 15 B, ICES-003, UL 1778

Sustainability	
Sustainability certificates	ENERGY STAR

Weight & dimensions	
Width	171 mm
Depth	439 mm
Height	219 mm
Weight	20.1 kg

Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	✔
Cold start	✔

Packaging data	
Package width	330 mm
Package depth	590 mm
Package height	330 mm
Package weight	22.6 kg

Logistics data	
Products per pallet	12 pc(s)

Other features	
Output voltage	120 V



0731304322764



731304322764

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 27-AUG-2026. Prints or copies of Information are only valid on the printed Publication date