



## APC Smart-UPS 2200VA LCD RM 2U 120V US uninterruptible power supply (UPS) 2.2 kVA 1980 W 8 AC outlet(s)



**Brand :** APC

**Product code:** SMT2200RMUS

**Product name :** Smart-UPS 2200VA LCD RM 2U 120V US




2200VA, 1920W, 120V, 6 x NEMA 5-15R & 2 x NEMA 5-20R, USB, SmartSlot, LCD, 2U, US  
APC Smart-UPS 2200VA LCD RM 2U 120V US. Output power capacity: 2.2 kVA, Output power: 1980 W, Waveform: Sine. AC outlet types: NEMA 5-15R, NEMA 5-20R, Power plug: NEMA 5-20P, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 5.4 min, Typical backup time at half load: 15.2 min. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 480 mm, Depth: 683 mm, Height: 86 mm

| Features                                       |                         | Battery                           |                                 |
|------------------------------------------------|-------------------------|-----------------------------------|---------------------------------|
| Output power capacity *                        | 2.2 kVA                 | Replacement battery cartridge     | RBC43                           |
| Output power *                                 | 1980 W                  | Design                            |                                 |
| Waveform *                                     | Sine                    | Form factor *                     | Rackmount                       |
| Input operation voltage (min) *                | 75 V                    | Rack capacity                     | 2U                              |
| Input operation voltage (max) *                | 154 V                   | Cable length                      | 2.44 m                          |
| Input frequency *                              | 50/60 Hz                | Product colour *                  | Black                           |
| Surge energy rating                            | 530 J                   | Display type                      | LCD                             |
| Efficiency                                     | 98%                     | Operational conditions            |                                 |
| Emergency Power Off (EPO)                      | ✓                       | Operating temperature (T-T)       | 0 - 40 °C                       |
| Output voltage Total Harmonic Distortion (THD) | 5%                      | Storage temperature (T-T)         | -15 - 45 °C                     |
| Noise level                                    | 55 dB                   | Operating relative humidity (H-H) | 0 - 95%                         |
| Audible alarm(s)                               | ✓                       | Storage relative humidity (H-H)   | 0 - 95%                         |
| Audible alarm modes                            | Battery replacement     | Operating altitude                | 0 - 3000 m                      |
| Ports & interfaces                             |                         | Non-operating altitude            | 0 - 15000 m                     |
| AC outlet types                                | NEMA 5-15R, NEMA 5-20R  | Weight & dimensions               |                                 |
| Power plug                                     | NEMA 5-20P              | Width                             | 480 mm                          |
| AC outlets quantity                            | 8 AC outlet(s)          | Depth                             | 683 mm                          |
| USB 2.0 ports quantity                         | 1                       | Height                            | 86 mm                           |
| Battery                                        |                         | Weight                            | 42.3 kg                         |
| Battery technology                             | Sealed Lead Acid (VRLA) | Packaging data                    |                                 |
| Typical backup time at full load               | 5.4 min                 | Package weight                    | 49.7 kg                         |
| Typical backup time at half load               | 15.2 min                | Other features                    |                                 |
| Battery recharge time                          | 3 h                     | Nominal output voltage            | 120 V                           |
|                                                |                         | Nominal input voltage             | 120 V                           |
|                                                |                         | Output connection type            | 6 x NEMA 5-15R & 2 x NEMA 5-20R |
|                                                |                         | Package dimensions (WxDxH)        | 600 x 980 x 254 mm              |



0731304305613



731304305613

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.