APC SRT1000RMXLA uninterruptible power supply (UPS) Double-conversion (Online) 1 kVA 900 W 6 AC outlet(s)

Brand : APC

Product code: SRT1000RMXLA

Product name : SRT1000RMXLA

1000 VA, 900 W, 50-150 V, 40/70 Hz, 432J, 3:1, 6 x NEMA 5-15R, 1.83m, IP20, 2U
APC SRT1000RMXLA. UPS topology: Double-conversion (Online), Output power capacity: 1 kVA, Output power: 900 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Certification: CSA C22.2 No.107.3-05,

Features	
UPS topology *	Double-conversion (Online)
Output power capacity *	1 kVA
Output power *	900 W
Waveform *	Sine
Input operation voltage (min) *	50 V
Input operation voltage (max) *	150 V
Input frequency *	40 - 70 Hz
Output frequency	50/60 Hz
Surge energy rating	432 J
Crest factor	3:1
Emergency Power Off (EPO)	✔
Output voltage Total Harmonic Distortion (THD)	2%
Audible alarm(s)	✔

Ports & interfaces	
AC outlet types	NEMA 5-15R
Power plug	NEMA 5-15P
AC outlets quantity	6 AC outlet(s)
USB port	✔
Serial interface	✔
Ethernet LAN (RJ-45) ports	1
SmartSlot	✔

Battery	
Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	1
Battery life (max)	5 year(s)
Battery recharge time	3 h
Automatic battery test	✔
Cold start	✔

Design	
Form factor *	Rackmount/Tower
Rack capacity	2U
Cable length	1.83 m

Design	
Product colour *	Black
Display type	LCD
LED indicators	Status
International Protection (IP) code	IP20

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates	
Certification	CSA C22.2 No.107.3-05,

Packaging content	
Cables included	USB cable
Quick installation guide	✔

Sustainability	
Sustainability certificates	ENERGY STAR


Weight & dimensions	
Width	432 mm
Depth	508 mm
Height	85 mm
Weight	22 kg

Packaging data	
Bracket	✔
Resource CD	✔
Warranty card	✔
Software CD	✔
Package width	594 mm
Package depth	749 mm
Package height	246 mm
Package weight	29.6 kg

Other features	
Output voltage	120 V



0731304329961



731304329961

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 27-AUG-2026. Prints or copies of Information are only valid on the printed Publication date