



Canon imageFORMULA DR-G2110 Sheet-fed scanner 600 x 600 DPI A3 Black, White

Brand : Canon

Product family:
imageFORMULA

Product code: 3150C002

Product name : DR-G2110

A3, CIS, 600 dpi, RGB LED, 500 sheets, RJ-45, USB 3.1

Canon imageFORMULA DR-G2110 Sheet-fed scanner 600 x 600 DPI A3 Black, White:

Fast and durable A3 production scanner

Optimised for customers who demand exceptional high-speed productivity, superior image quality and dependable feeding performance, this A3 scanner is robust, simple to use and performs quietly

Productivity

Ultra-efficient scanner delivers up to 220 images per minute

Image quality

Advanced image-processing tools deliver consistently crisp, clear, high-quality images

Reliable

Robust, durable paper feed and transport rollers – delivers up to 30,000 scans per day



Scanning		Paper handling	
Maximum scan size *	305 x 432 mm	Auto Document Feeder (ADF) media weight	20 - 209 g/m ²
Optical scanning resolution *	600 x 600 DPI	Maximum scan length	5.59 m
Colour scanning	✓	Ports & interfaces	
Duplex scanning *	✓	USB port *	✓
ADF scan speed (b/w, A3)	120 ppm	USB version	3.2 Gen 2 (3.1 Gen 2)
ADF scan speed (colour, A3)	120 ppm	Standard interfaces	RJ-45, USB 3.2 Gen 1 (3.1 Gen 1)
Duplex ADF scan speed (b/w, A4)	240 ipm	Network	
Duplex ADF scan speed (colour, A4)	240 ipm	Ethernet LAN	✓
Design		Power	
Scanner type *	Sheet-fed scanner	Power supply type *	AC
Product colour *	Black, White	Power consumption (typical)	66.5 W
Built-in display *	✓	AC input frequency	50 - 60 Hz
Performance		Input voltage	220 - 240 V
Sensor type *	CIS	Power consumption (sleep)	3.5 W
Light source	RGB LED	Weight & dimensions	
Daily duty cycle (max) *	50000 pages	Width	480 mm
Scan drivers	ISIS, Kofax VRS, TWAIN, WIA	Depth	569 mm
Scanning noise level	54 dB	Height	315 mm
Input capacity		Weight	25 kg
Standard input capacity	500 sheets	Sustainability	
Paper handling		Sustainability certificates	EPEAT Gold
Long-paper mode	✓	Operational conditions	
Maximum ISO A-series paper size *	A3	Operating temperature (T-T)	10 - 35 °C
		Operating relative humidity (H-H)	20 - 80%
		Operating temperature (T-T)	50 - 95 °F



0013803308921



013803308921

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.