Canon imageFORMULA DR-G2140 Sheet-fed scanner 600 x 600 DPI A3 Black, White

Brand : Canon

Product family: imageFORMULA

Product code: 3149C009

Product name : DR-G2140

A3, CIS, 600 dpi, RGB LED, 500 sheets, USB 3.1

Canon imageFORMULA DR-G2140 Sheet-fed scanner 600 x 600 DPI A3 Black, White:

Ultra-fast model takes production scanning to the next level

Optimised for customers who require exceptional high-speed productivity, superior image quality and dependable feeding performance, this A3 scanner has been created to excel in demanding environments

Productivity
Ultra-efficient scanner outputs up to 280 images per minute

Reliability
Robust, durable paper feed and transport rollers can deliver up to 70,000 scans per day

Image quality
Advanced image-processing tools deliver consistently crisp, clear, high-quality images

Scanning	
Maximum scan size *	305 x 432 mm
Optical scanning resolution *	600 x 600 DPI
Colour scanning	✔
Duplex scanning *	✔
Output colour depth	24 bit
Output greyscale depth	8 bit
ADF scan speed (b/w, A3)	145 ppm
ADF scan speed (colour, A3)	145 ppm
Duplex ADF scan speed (b/w, A4)	290 ipm
Duplex ADF scan speed (colour, A4)	290 ipm

Design	
Scanner type *	Sheet-fed scanner
Product colour *	Black, White
Built-in display *	✔

Performance	
Sensor type *	CIS
Light source	RGB LED
Daily duty cycle (max) *	70000 pages
Scan drivers	ISIS, TWAIN, WIA
Scanning noise level	54 dB

Input capacity	
Standard input capacity	500 sheets

Paper handling	
Long-paper mode	✔
Maximum ISO A-series paper size *	A3
Auto Document Feeder (ADF) media weight	20 - 209 g/m²

Ports & interfaces	
USB port *	✔
USB version	3.2 Gen 2 (3.1 Gen 2)
Standard interfaces	USB 3.2 Gen 1 (3.1 Gen 1)

Power	
Power supply type *	AC
Power consumption (typical)	66.5 W
AC input frequency	50 - 60 Hz
Sleep mode	✔
Input voltage	220 - 240 V
Power consumption (sleep)	3.5 W

Weight & dimensions	
Width	480 mm
Depth	569 mm
Height	315 mm
Weight	25 kg

Packaging content	
Bundled software	Canon CaptureOnTouch, Kofax VRS Professional

Sustainability	
Sustainability certificates	EPEAT Gold

System requirements	
Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1
Server operating systems supported	Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016

Operational conditions	
Operating temperature (T-T)	10 - 35 °C
Operating relative humidity (H-H)	20 - 80%
Operating temperature (T-T)	50 - 95 °F

0013803315103

013803315103

Catalog Object Cloud

Publication date: 06-SEP-2026. Prints or copies of Information are only valid on the printed Publication date