



Canon imageFORMULA DR-G2090 Sheet-fed scanner 600 x 600 DPI A3 Black, White

Brand : Canon

Product family:
imageFORMULA

Product code: 3151C002

Product name : DR-G2090

A3, CIS, 600 dpi, RGB LED, 300 sheets, USB 3.1

Canon imageFORMULA DR-G2090 Sheet-fed scanner 600 x 600 DPI A3 Black, White:

Ultra-fast model takes A3 production scanning to the next level

Optimised for customers who demand exceptional high-speed productivity, superior image quality and dependable feeding performance, this A3 scanner is robust, simple to use and performs quietly

Productivity

Ultra-efficient scanner outputs up to 180 images per minute

Image quality

Advanced image-processing tools deliver consistently crisp, clear, high-quality images

Reliability

Robust, durable paper-feed and transport rollers – delivers up to 30,000 scans per day



Scanning		Paper handling	
Maximum scan size *	305 x 432 mm	Maximum ISO A-series paper size *	A3
Optical scanning resolution *	600 x 600 DPI	Auto Document Feeder (ADF) media weight	20 - 209 g/m ²
Colour scanning	✓	Maximum scan length	3 m
Duplex scanning *	✓	Ports & interfaces	
Output colour depth	24 bit	USB port *	✓
Output greyscale depth	8 bit	USB version	3.2 Gen 2 (3.1 Gen 2)
Duplex ADF scan speed (b/w, A4)	200 ipm	Standard interfaces	USB 3.2 Gen 1 (3.1 Gen 1)
Duplex ADF scan speed (colour, A4)	200 ipm	Power	
Design		Power supply type *	AC
Scanner type *	Sheet-fed scanner	Power consumption (typical)	66.5 W
Product colour *	Black, White	AC input frequency	50 - 60 Hz
Built-in display *	✓	Input voltage	220 - 240 V
Performance		Power consumption (sleep)	3.5 W
Sensor type *	CIS	Weight & dimensions	
Light source	RGB LED	Width	480 mm
Daily duty cycle (max) *	30000 pages	Depth	569 mm
Scan drivers	Kofax VRS, ISIS, TWAIN, WIA	Height	315 mm
Scanner error detection	✓	Weight	25 kg
Scanning noise level	54 dB	Sustainability	
Input capacity		Sustainability certificates	EPEAT Gold
Standard input capacity	300 sheets	Operational conditions	
Paper handling		Operating temperature (T-T)	10 - 35 °C
Long-paper mode	✓	Operating relative humidity (H-H)	20 - 80%
		Operating temperature (T-T)	50 - 95 °F



0013803310146



013803310146

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.