



Canon imageFORMULA DR-M1060II Sheet-fed scanner 600 x 600 DPI A3 Black

Brand : Canon

Product code: 6049C002

Product name : imageFORMULA DR-M1060II

60ppm/120ipm, 600 dpi, USB, 424 (W) x 246 (D) x 120 (H) mm

Canon imageFORMULA DR-M1060II Sheet-fed scanner 600 x 600 DPI A3 Black:

A uniquely compact, eco-friendly and reliable A3 desktop scanner that helps creating smooth workflows and capturing multiple document types and formats.

Superior efficiency from a uniquely compact A3 scanner

Enjoy quick and effortless scanning with the high-speed, high-quality imageFORMULA DR-M1060II. Save time with easy maintenance and deliver enhanced sustainability via a compact device.

Canon imageFORMULA DR-M1060II. Optical scanning resolution: 600 x 600 DPI, Output colour depth: 24 bit, Output greyscale depth: 8 bit. Scanner type: Sheet-fed scanner, Product colour: Black. Sensor type: CIS, Daily duty cycle (max): 13000 pages, Light source: RGB LED. Maximum ISO A-series paper size: A3, Scanning media types supported: Business Card, Plastic Card, Media thickness (min): 0.04 mm. USB version: 2.0/3.2 Gen 1 (3.1 Gen 1)



Scanning		Ports & interfaces	
Optical scanning resolution *	600 x 600 DPI	USB port *	✓
Duplex scanning *	✓	USB version	2.0/3.2 Gen 1 (3.1 Gen 1)
Output colour depth	24 bit	Power	
Output greyscale depth	8 bit	Power supply type *	AC
Design		Power consumption (typical)	32.5 W
Scanner type *	Sheet-fed scanner	AC input frequency	50/60 Hz
Product colour *	Black	Sleep mode	✓
Built-in display *	✗	Power consumption (sleep)	1.9 W
Performance		Weight & dimensions	
Sensor type *	CIS	Width	424 mm
Light source	RGB LED	Depth	440 mm
Daily duty cycle (max) *	13000 pages	Height	210 mm
Paper handling		Weight	6.1 kg
Scanning media types supported	Business Card, Plastic Card	Folded width	42.4 cm
Long-paper mode	✓	Folded depth	24.6 cm
Maximum ISO A-series paper size *	A3	Folded height	12 cm
Media thickness (min)	0.04 mm	Operational conditions	
Maximum scan width	30 cm	Operating temperature (T-T)	10 - 32.5 °C
Maximum scan length	3 m	Operating relative humidity (H-H)	20 - 80%



0013803371734



013803371734

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.